Surface Mount

RF Transformer

T1-6-KK81+ T1-6-KK81

0.01 to 150 MHz


Maximum Ratings

Operating Temperature	-20°C to 85°C
Storage Temperature	-55°C to 100°C
RF Power	250mW
DC Current	30mA
Pormonant damage may occur if any	of those limits are evenedo

Pin Connections


PRIMARY DOT	4
PRIMARY	6
SECONDARY DOT	3
SECONDARY	1
SECONDARY CT	_
NOT USED	2,5

Outline Drawing



Outline Dimensions (inch)

.30	.27	.23	.010	.042	.020	.100	.05	J .05 1.27
.020	.036	.26	.575	P .600 15.24	.125	.050	.100	



Features

- good return loss
- also available with plug-in (X65) and flat-pack (W38) leads

CASE STYLE: KK81 PRICE: \$5.65 ea. QTY (1-9)

+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

Applications

- HF/VHF
- receivers/transmitters


Transformer Electrical Specifications


Ω RATIO	FREQUENCY (MHz)	INSERTION LOSS*			
		3 dB MHz	2 dB MHz	1 dB MHz	
1	0.01-150	0.01-150	0.02-100	0.05-50	

^{*} Insertion Loss is referenced to mid-band loss, 0.15 dB typ.

Typical Performance Data

71			
FREQUENCY (MHz)	INSERTION LOSS (dB)	INPUT R. LOSS (dB)	
0.01	1.53	3.51	
0.02	0.58	7.36	
0.05	0.18	14.35	
0.10	0.13	20.32	
0.20	0.13	26.00	
50.00	0.54	9.38	
76.89	0.97	6.19	
100.00	1.37	4.61	
143.59	2.26	2.79	
150.00	2.43	2.57	





- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.

 B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.

 C. The parts covered by this specification document are subject to Mini-Circuit satandard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp